



PRODUCT INFORMATION

SUPER 10OUTBOARD MOTOR OIL

CHARACTERISTICS

Outboard Motor Oil belongs to a new generation of sophisticated high performance oils featuring outstanding properties.

Outboard Motor Oil has been developed using top quality base oils with the addition of special additives.

QUALITIES & ADVANTAGES

- Has been especially developed as automatic lubricating two stroke engine oil and is listed as a super outboard type.

SPECIFICATION:

Outboard Motor Oil meets and exceeds the following:

NMMA BIA-Service TC-WIII

TYPICAL ADDITION PERCENTAGES:

Outboard Motor Oil is mixed in a typical proportion of 2% of a 1:50 oil/petrol mixing ratio.

PHYSICAL DATA

VISCOSITY mm ² /s at 40°C	38
VISCOSITY mm ² /s at 100°C	7.0
VISCOSITY INDEX	130
POUR POINT, °C	-35
FLASH POINT COC, °C	260
SPEC. GRAVITY Kg/ltr	0.879
SULPHATE ASH, %	0.01

AREAS OF APPLICATION:

Outboard Motor Oil is recommended for all types of water and air-cooled two-stroke engines such as:

- Outboard motors, jet skies
- Motor sleighs
- Motorbikes, scooters, mopeds
- Lawn mowers
- Chain saws

** Delta Oil Gas Conditioner can be added for lower wear and tear and longer engine life. Typical addition percentages will be 10 ml Gas Conditioner/ 10 Ltr fuel.

SAFETYFAX

Avoid prolonged contact with skin.

- Keep away from children.
- If swallowed, do not induce vomiting - call a doctor.
- Do not inhale fumes.
- Do not dispose of empty oil cans or oil waste in the environment.