



PRODUCT INFORMATION

SUPER 1 MOTOR OIL SAE 0W30

CHARACTERISTIC

Super 1 Motor Oil SAE 0W30 is special formulated fully synthetic engine oil of the latest generation recommended for the lubrication of all gasoline and diesel engines.

Super 1 Motor Oil SAE 0W30 is special formulated added selective FMA additives.

Super 1 Motor Oil SAE 0W30 can be mixed with all other types of motor oils.

ADVANCED PROPERTIES

- Excellent fluidity at low temperature.
- Immediate lubrication after starting.
- Fuel Economy.
- Very high thermal stability.
- Reduces wear and deposits.

ANTI WEAR PROPERTIES

Extreme low friction and reduced wear and tear compared with conventional oils.

APPLICATION:

- 4-stroke gasoline engines, multi-valves, turbo.
- 4-stroke diesel engines, with or without turbo.

SPECIFICATIONS:

EXCEED SPECIFICATIONS

SAE 0W30

API SL/CF, SM

ACEA A3/B4

MIL-L 2104B

MIL-L 46152B

MB 229.3 VW 502.00 505.00

BMW LL-98

OPEL GM-LL-B-025

RENAULT RN 0700, RN 0710

DATA

| | |
|-----------------------------------|-----------|
| Density at 15°C kg/m ³ | 855 |
| Viscosity (cSt) at 40°C | 62 |
| Viscosity (cSt) at 100°C | 11,0 |
| Viscosity (cP) at -35°C | 5900 |
| Viscosity index | 171 |
| Flash point COC, °C | 220 |
| Pour point °C | Under ÷50 |
| TBN g/KOH kg | 10,6 |
| Sulphated ash, mass % | 1,1 |