



## PRODUCT INFORMATION

# SUPER 1 MOTOR OIL SAE 5W40

---

### CHARACTERISTIC

Super 1 Motor Oil SAE 5W-40 is special formulated synthetic motor oil in the High Performance range of products recommended to diesel and gasoline/petrol/benzin engines, Diesel Engines with and without turbo, the recommendation covers all types of engines and represent the highest technology.

Can be used under a wide range of operating temperatures also at extreme low temperatures a secured start and low energy and fuel consumption can be noticed.

Super 1 Motor Oil SAE 5W-40 is special formulated added selective FMA additives.

Super 1 Motor Oil SAE 5W-40 can be mixed with all other types of motor oils.

### ADVANCED PROPERTIES

- Secured lubrication of all moving components at all temperatures.
- Float properties at extreme low temperatures.
- Low friction at any start.
- High viscosity index.
- High temperature stability.

### ANTI WEAR PROPERTIES

Extreme low friction and reduced wear and tar compared with conventional oils.

### RECOMMENDED:

- All type engines with or without turbo and catalysed systems, all new euro 4 engines.
- Recommended for Gasoline and Diesel engines.

### SPECIFICATIONS:

#### EXCEED SPECIFICATIONS

SAE 5W-40

API SN/CF/EC CI 4 (Energy Conserving)

ACEA A3/ B4-08 ISSUE 2 E4-08 Issue E7-08 issue 2

MIL-L 2104B

MIL-L 46152B

MB 226.5 - 228.5

MAN M3277

OPEL GM-II-B-025

RENAULT RXD

VOLVO VDS-3

MTU type 3

RENAULT RLD-2

RENAULT RN 0700

RENAULT RN 0710

DAF extended drain

MACK EO-N Premium plus

VW 505 00

BMW longlife-01

PSA B71 2296

MB 229.3

MB 226.5

PORSCHE A40

## SUPER 1 MOTOR OIL SAE 5W40 - continued

---

### DATA

Gravity v/15°C KG/L	0.855
Viscosity (cSt) v/100°C	13.8
Viscosity index	160 min.
Flash point COC, °C	235
Pour point °C	÷45
TBN	8.8