



PRODUCT INFORMATION

UNI TRAC STOU SAE 15W30

CHARACTERISTICS:

Uni Trac Stou Oil belong to a new generation of high performance oils and a special developed multi product for Agro Culture machines, Tractors, Hydraulics, etc. and Contractor machines, a top quality product with long life properties, an all year type of oil.

Uni Trac Stou Oil has been developed on selected base oils and special additives to insure special friction characteristics and reduced wear and tear.

Uni Trac Stou Oil is a semi synthetic oil formulated as a universal oil to exceed the most stringent quality requirements as a Motor oil suitable for Petrol and Diesel engines with & without Turbo and to all combined transmission and hydraulic systems also with "wet brakes".

Uni Trac Stou Oil is formulated to exceed demands from major machinery manufactures.

Uni Trac Stou Oil is an all year type of oil with security for easy start at all temperatures.

QUALITIES & ADVANTAGES

- Shows with High Performance properties reduction of coke build up and normal increase of wear particles.
- Special friction characteristics lead to optimised economy and fuel savings.
- An all year type of oil for the total machinery in the agro or contractor field.

- Eliminate problems with piston rings, hanging valves and minimize coke formation in chamber.
- Very effective detergent and dispersant properties for easy maintenance.
- Longer lifetime on all components and equipment.
- Reduced noise from "wet brakes" and lower operating temperatures on the loaded hydraulic system, longer lifetime.

ANTI-WEAR & TEAR QUALITIES

- Excellent Anti Wear properties. Long life engine perspectives.

ANTI-CORROSION

- Oxidation stability.
- Anti Corrosion properties.

APPLICATION

- Agro culture machinery, contractors.
- Hydraulic systems.
- Transmissions.
- Gear transmissions and differentials.
- Wet brakes.

SAFETYFAX

- Avoid prolonged skin contact.
- Keep petrochemicals away from children.
- If swallowed, do not induce vomiting – call a doctor.
- Do not inhale fumes.
- Do not dispose empty oil cans or oil waste in-the-environment.

UNI TRAC STOU SAE 15W30

- continued

SPECIFICATIONS:

Uni Trac Stou Oil exceeds the specifications:

ACEA E4-02

- MIL-L 46152 B
- MIL-L 2104 D
- MIL-L 2105 D

API CG-4

API GL-4

FORD ESN-M2C-159B/C

JD J27

MF M 1145

ALLISON C4

API GL 4

API GL 5 (low speed/high torque)

API SF/CE

FORD ESN-M2C134 CD

FORD ESN-M2C159 B/C

FORD FNH 82009202

MB 227.1

ALLISON C4 (agriculture applic.)

MAN 271

ACEA E3

CASE MAT 3525

CASE MAT 3526

JD J20C

MF M 1135

MF M 1139

MF M 1143

MF M 1144

NH NH 030C

ZF TE-MI 03A

ZF TE-MI 05K

ZF TE-MI 06a

ZF TE-MI 06B

ZF TE-MI 06C

ZF TE-MI 07B

ZF TE-MI 07D

AFNOR NFE 68-603 E

Sauer Sunstrand/
Danfoss

Hydro Static Trans Fluid

EATON VICKERS I-280-S

EATON VICKERS M-2950-S

PHYSICAL DATA

SAE-GRADE	15W30
VISCOSITY (CSt) mm ² /s v/40°C	81,7
VISCOSITY (CSt) mm ² /s v/100°C	10,6
VISCOSITYINDEX	125 MIN.
POURPOINT, °C	-39
FLASHPOINT	216
GRAVITY v/20°C	0,886
TBN, D-2896 mg KOH/g	10,2